

Highbay Luminaires

Lamp Watts	Base	Reflector (Diameter)	¾" Pendant Mount Standard Profile ①
Metal Halide			
175	Mogul	18"	HB5-175MH-TT ②
250	Mogul	18"	HB5-250MH-TT ②
400	Mogul	18"	HB5-400MH-TT
1000	Mogul	22"	HB5-1000MH-TT
High Pressure Sodium			
150	Mogul	18"	HB5-150HP-TT
250	Mogul	18"	HB5-250HP-TT
400	Mogul	18"	HB5-400HP-TT
1000	Mogul	22"	HB5-1000HP-TT

① 120V / 277V / 347V Tri-Tap ballast listed — for other voltages consult factory.
 ② Must use bottom closure or protected lamp See "Options - Lamp."

Options

to order add suffix	Suffix
Lamp	<i>Consult Factory</i>
Coated lamp recommended	
Items noted "②" above must have either a bottom closure and standard lamp or protected lampholder and protected lamp.	
To order with bottom closure	<i>see accessories</i>
To order with lampholder for protected lamp	
Order lamp separately	-PLS
Pulse Start Luminaires High Performance Metal Halide	
For 175W, 250W, 400W MH	-PSB
For 200W, 320W, 350W, 450W	<i>Standard</i>
Potted Ballasts	
For low noise requirements	-POT
Quartz Auxiliary	
Quartz lamp not included	-Q
Protected Ignitor	
For HPS luminaires	-PI
Fuse Holder	
Supplied with fuse	
Single pole	-F1
Accu-Flex™	<i>page 11</i>

Accessories

Order separately	Catalogue #
Safety Hook	
Not recommended for Low Profile ¾" NPT	
Male	HK75SS
Female	HF75SS
Cord Set	
3 conductor, Type ST105	
3' long	Cord only 3C
	Cord & plug 3CP
<i>For lengths other than 3 feet, revise the 3 in the catalogue number to the length in feet.</i>	
Q-Deck Plate	
For quick mounting	
Mounting screws not included	Q-DECK
Bottom Closure	
For 18" reflector	HB5-BL18
For 22" reflector	HB5-BL22
Top Shroud	HB5-SS
Ballast Safety Chain	HB5-BSC
Optical Assembly Safety Cable	HB5-RSC
Wire Guard	
For 18" reflector	HB5-WG18
For 22" reflector	HB5-WG22

HB5

Economy Cast fixtures with 18" and 22"



Cast Housing

Economical die cast aluminum ballast, not sheet metal. Natural finish.

Easy Install Mounting

Extra large junction box with slide top adapter.

Full Range of Accessories

Gemini™ is available with most common accessories including fusing, quartz auxiliary lights, hooks, lens and guards.

Adjustable Beam Spread

18" and 22" diffused aluminum reflectors are adjustable for narrow, medium and wide beam spreads.

New Technology Pulse Start Metal Halide Lamps & Ballasts

Pulse Start technology provides longer lamp life, more lumens per watt, better lumen maintenance, faster lamp warm up, faster hot restrike and superior colour rendition.


Socket

Specification grade porcelain lampholder.

Ballasts

HPF ballasts are suitable low temperature starting. MH-30°C, Pulse Start MH -40°C, HPS -40°C

To 400 watt
¾" Hub



1000 watt
¾" Hub

