

FLL

1000 Watt



Lamp Watts	Base	Yoke Mount ①	Slipfitter ①
Metal Halide			
1000	Medium	FLL1000MH-TT	FLL1000MH-TT-SF
High Pressure Sodium			
400	Medium	FLL1000HP-TT	FLL1000HP-TT-SF

① 120V / 277V / 347V Tri-Tap ballast listed — for other voltages consult factory.

Options

To order add suffix	Suffix
Lamp With clear lamp	-L
Photocontrol	-PC
Protected Ignitor For HPS luminaires	-PI
Fuse Holder Supplied with fuse	-F1
	Single Pole

Accessories

Order separately Catalogue #	
Tenon Adapter Converts yoke to slipfitter Tenon 2" IPS (2 3/8" OD)	FLL-TA
Cross Arm Adapter For horizontal aiming	FLL-CA
Vandal Shield Lexan	FLL-LS
Top Visor	FLL-TV
Wall Bracket Use with slipfitter or tenon adapter Tenon 2" IPS (2 3/8" OD)	WB-1-BZ

Compact

With an EPA of 4.1 ft², Accuflood™ FLL floodlights are a compact high wattage floodlight.

Construction

Full seam welded construction.

Removable ballast tray.

One Piece fabricated door assembly.

Flat tempered glass lens.

Mounting

Choice of yoke or slipfitter mounting.

Socket

Specification grade porcelain lampholder.

Finish

Bronze polyester powder coat finish.

Ballasts

HPF ballasts are suitable low temperature starting.
MH-30°C, HPS -40°C

