


Fluorescent Lamps



T8 Medium Bipin



T8 Single Pin Slimline



T8 Recessed D.C.

Nominal Lamp Watts	Product Number 046677-	Ordering Code	Pkg. Qty.	Description	Nom. Length (In.)(212)	Avg. Life, Hrs. (224)	Approx.: Int.(203) Lum.(204)	Design Lumens (208)	CRI
--------------------	------------------------	---------------	-----------	-------------	------------------------	-----------------------	------------------------------	---------------------	-----

Rapid Start Fluorescent Lamps T8 Medium Bipin

32	Ⓜ ⓈⓈⓈ	27252-6	F32T8/TL730/ALTO	25	TL 70, 3000K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27282-3	F32T8/TL730/ALTO PLZ	1350	TL 70, 3000K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27228-1	F32T8/TL730/ALTO UPC	25	TL 70, 3000K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27249-2	F32T8/TL735/ALTO	25	TL 70, 3500K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27259-1	F32T8/TL735/ALTO PLZ	1350	TL 70, 3500K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27274-0	F32T8/TL735/ALTO UPC	25	TL 70, 3000K featuring Hi-Vision™ Phosphor(225)	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27248-4	F32T8/TL741/ALTO	25	TL 70, 4100K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27255-9	F32T8/TL741/ALTO PLZ	1350	TL 70, 4100K featuring Hi-Vision™ Phosphor	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27269-0	F32T8/TL741/ALTO UPC	25	TL 70, 3000K featuring Hi-Vision™ Phosphor(225)	48	20,000	2800	2660	78
	Ⓜ ⓈⓈⓈ	27268-2	F32T8/TL750/ALTO	25	TL 70, 5000K featuring Hi-Vision™ Phosphor	48	20,000	2750	2550	78
40	ⓈⓈⓈ	31996-2	F40T8/TL830	25	TL 80, 3000K	60	20,000	3775	3500	85
	ⓈⓈⓈ	25799-8	F40T8/TL835	25	TL 80, 3500K	60	20,000	3775	3500	85
	ⓈⓈⓈ	31998-8	F40T8/TL841	25	TL 80, 4100K	60	20,000	3775	3500	84
	ⓈⓈⓈ	32057-2	F40T8/TL730	25	TL 70, 3000K	60	20,000	3600	3250	75
	ⓈⓈⓈ	32301-4	F40T8/TL735	25	TL 70, 3500K	60	20,000	3600	3250	75
	ⓈⓈⓈ	32058-0	F40T8/TL741	25	TL 70, 4100K	60	20,000	3600	3250	75

U-Bent Rapid Start Fluorescent Lamps T8 Medium Bipin with 6" long spacing (212).

32	ⓈⓈⓈ	34080-2	FB32T8/TL830/6	20	TL 80, 3000K	22 ^{7/16}	20,000	2800	2535	85
	ⓈⓈⓈ	34084-4	FB32T8/TL835/6	20	TL 80, 3500K	22 ^{7/16}	20,000	2800	2535	85
	ⓈⓈⓈ	34088-5	FB32T8/TL841/6	20	TL 80, 4100K	22 ^{7/16}	20,000	2800	2535	85
	ⓈⓈⓈ	20927-0	FB32T8/TL850/6	20	TL 80, 5000K	22 ^{7/16}	20,000	2750	2500	84
	ⓈⓈⓈ	34073-7	FB32T8/TL730/6	20	TL 70, 3000K	22 ^{7/16}	20,000	2650	2370	75
	ⓈⓈⓈ	34077-8	FB32T8/TL735/6	20	TL 70, 3500K	22 ^{7/16}	20,000	2650	2370	75
	ⓈⓈⓈ	34079-4	FB32T8/TL741/6	20	TL 70, 4100K	22 ^{7/16}	20,000	2650	2370	75
	ⓈⓈⓈ	20928-8	FB32T8/TL750/6	20	TL 70, 5000K	22 ^{7/16}	20,000	2600	2325	75

Instant Start Fluorescent Lamps T8 Single Pin

59	ⓈⓈⓈ	34457-2	F96T8/TL830	24	TL 80, 3000K	96	15,000	5900	5490	85
	ⓈⓈⓈ	34460-6	F96T8/TL835	24	TL 80, 3500K	96	15,000	5900	5490	85
	ⓈⓈⓈ	34462-2	F96T8/TL841	24	TL 80, 4100K	96	15,000	5900	5490	85
	ⓈⓈⓈ	21479-1	F96T8/TL850	24	TL 80, 5000K	96	15,000	5780	5375	84
	ⓈⓈⓈ	34453-1	F96T8/TL730	24	TL 70, 3000K	96	15,000	5700	5190	75
	ⓈⓈⓈ	34455-6	F96T8/TL735	24	TL 70, 3500K	96	15,000	5700	5190	75
	ⓈⓈⓈ	34456-4	F96T8/TL741	24	TL 70, 4100K	96	15,000	5700	5190	75
	ⓈⓈⓈ	21477-5	F96T8/TL750	24	TL 70, 5000K	96	15,000	5580	5080	75

ⓈⓈⓈ — Energy Saving Product
 Highest Color Rendering Lamps (CRI ≥ 80)
 Features ALTO® Lamp Tech. High Color Rendering Lamps (CRI 70-79)

Ⓢ Means This Bulb Meets US Federal Minimum Efficiency Standard Ⓜ This lamp features ALTO Lamp Technology

For maximum energy-efficiency with Fluorescent Lamps use Philips Electronic Ballasts, refer to catalog P-5277 for ordering information

T8 FLUORESCENT