



# Fluorescent Lamps



T8 Recessed D.C.



T8 Medium Bipin



T8

FLUORESCENT

Nominal Lamp Watts	Product Number 046677-	Ordering Code	Pkg. Qty.	Description	Nom. Length (In.)(212)	Avg. Life, Hrs.	Approx.: Int.(203) Lum.(204)	Design Lumens (208)	CRI
--------------------	------------------------	---------------	-----------	-------------	------------------------	-----------------	------------------------------	---------------------	-----

## High Output Fluorescent Lamps T8 Recessed Double Contact

<b>44</b>	†\$\$\$	28299-6	<b>F48T8/TL830/HO</b>	24	TL 80, 3000K	48	18,000	4000	3600	85
	†\$\$\$	28306-9	<b>F48T8/TL835/HO</b>	24	TL 80, 3500K	48	18,000	4000	3600	85
	†\$\$\$	28309-3	<b>F48T8/TL841/HO</b>	24	TL 80, 4100K	48	18,000	4000	3600	85
	†\$\$\$	28268-1	<b>F48T8/TL730/HO</b>	24	TL 70, 3000K	48	18,000	3800	3420	75
	†\$\$\$	28273-1	<b>F48T8/TL735/HO</b>	24	TL 70, 3500K	48	18,000	3800	3420	75
	†\$\$\$	28282-2	<b>F48T8/TL741/HO</b>	24	TL 70, 4100K	48	18,000	3800	3420	75
<b>55</b>	†\$\$\$	28316-8	<b>F60T8/TL830/HO</b>	24	TL 80, 3000K	60	18,000	5050	4545	85
	†\$\$\$	28317-6	<b>F60T8/TL835/HO</b>	24	TL 80, 3500K	60	18,000	5050	4545	85
	†\$\$\$	28320-0	<b>F60T8/TL841/HO</b>	24	TL 80, 4100K	60	18,000	5050	4545	85
	†\$\$\$	28283-0	<b>F60T8/TL730/HO</b>	24	TL 70, 3000K	60	18,000	4800	4320	75
	†\$\$\$	28286-3	<b>F60T8/TL735/HO</b>	24	TL 70, 3500K	60	18,000	4800	4320	75
	†\$\$\$	28291-3	<b>F60T8/TL741/HO</b>	24	TL 70, 4100K	60	18,000	4800	4320	75
<b>65</b>	†	28324-2	<b>F72T8/TL830/HO</b>	24	TL 80, 3000K	72	18,000	6100	5490	85
	†	28325-9	<b>F72T8/TL835/HO</b>	24	TL 80, 3500K	72	18,000	6100	5490	85
	†	29326-7	<b>F72T8/TL841/HO</b>	24	TL 80, 4100K	72	18,000	6100	5490	85
	†	28293-9	<b>F72T8/TL730/HO</b>	24	TL 70, 3000K	72	18,000	5800	5220	75
	†	28296-2	<b>F72T8/TL735/HO</b>	24	TL 70, 3500K	72	18,000	5800	5220	75
	†	28297-0	<b>F72T8/TL741/HO</b>	24	TL 70, 4100K	72	18,000	5800	5220	75
<b>86</b>	ⓔ □ \$\$\$	20513-8	<b>F96T8/TL830/HO</b>	24	TL 80, 3000K	96	18,000	8200	7625	85
	ⓔ □ \$\$\$	20514-6	<b>F96T8/TL835/HO</b>	24	TL 80, 3500K	96	18,000	8200	7625	85
	ⓔ □ \$\$\$	20515-3	<b>F96T8/TL841/HO</b>	24	TL 80, 4100K	96	18,000	8200	7625	85
	ⓔ □ \$\$\$	20508-8	<b>F96T8/TL730/HO</b>	24	TL 70, 3000K	96	18,000	7900	7100	75
	ⓔ □ \$\$\$	20511-2	<b>F96T8/TL735/HO</b>	24	TL 70, 3500K	96	18,000	7900	7100	75
	ⓔ □ \$\$\$	20512-0	<b>F96T8/TL741/HO</b>	24	TL 70, 4100K	96	18,000	7900	7100	75

## Preheat Fluorescent Lamps T8 Medium Bipin (requires use of starters).

<b>13</b>		25910-1	<b>F13T8/CW</b>	24	Cool White, 4100K	12	7500	500	400	62
<b>15</b>		31515-0	<b>F15T8/30U</b>	24	Ultralume, 3000K	18	7500	1000	910	85
		31516-8	<b>F15T8/41U</b>	24	Ultralume, 4100K	18	7500	1000	910	85
	□	31519-2	<b>F15T8/50U</b>	24	Ultralume, 5000K	18	7500	1000	910	85
		25441-7	<b>F15T8/HL WX</b>	24	Home Light Warm Deluxe, 3000K, Sleeved	18	7500	1000	910	85
		34286-5	<b>F15T8/C50</b>	24	ColorTone 50, 5000K	18	7500	590	500	92
		25853-3	<b>F15T8/SPEC35</b>	24	SPEC, 3500K	18	7500	940	825	73
		25952-3	<b>F15T8/D</b>	24	Daylight, 6500K	18	7500	750	660	79
		36996-7	<b>F15T8/D</b>	96	Daylight, 6500K	18	7500	750	660	79
		25946-5	<b>F15T8/WW</b>	24	Warm White, 3000K	18	7500	870	740	53
		25936-6	<b>F15T8/CW</b>	24	Cool White, 4100K	18	7500	870	765	62
		24991-2	<b>F15T8/HL Cool</b>	24	Home Light Cool, 4100K, Sleeved	18	7500	870	765	62
		27106-4	<b>F15T8/HL Cool</b>	6	Home Light Cool, 4100K, Sleeved	18	7500	870	765	62
		24987-0	<b>F15T8/HL Cool</b>	24	Home Light Cool, 4100K, Sleeved	24	7500	1175	940	62
		36436-4	<b>F15T8/CW</b>	96	Cool White, 4100K, Bulk Pack	18	7500	870	765	62
	25460-7	<b>F15T8/AGRO</b>	6	Agro-Lite, Sleeved	18	7500	410	—	—	
<b>30</b>		26063-8	<b>F30T8/D</b>	24	Daylight, 6500K	36	7500	1500	1350	79
		26058-8	<b>F30T8/WW</b>	24	Warm White, 3000K	36	7500	2260	2050	53
		26050-5	<b>F30T8/CW</b>	24	Cool White, 4100K	36	7500	2200	2000	62
		24986-2	<b>F30T8/HL Cool</b>	24	Home Light Cool, 4100K, Sleeved	36	7500	2200	2000	62
		27124-7	<b>F30T8/HL Cool</b>	6	Home Light Cool, 4100K, Sleeved	36	7500	2200	2000	62

□ Exclusive Philips Products

\$\$\$ — Energy Saving Product

■ Highest Color Rendering Lamps (CRI ≥ 80)

† New Since Last Printing

■ High Color Rendering Lamps (CRI 70-79)

ⓔ Means This Bulb Meets US Federal Minimum Efficiency Standard

**For maximum energy-efficiency with Fluorescent Lamps use Philips Electronic Ballasts, refer to catalog P-5277 for ordering information**