

6

# OPL



OPTILUX 2' x 2' air handling luminaires.

Air functions, cold air supply / return, static, or heat removal.

Recessed air aperture along 2 sides of luminaire housing.


Precision formed, 4 1/4" deep cell low iridescent specular aluminum louver.

Louver assembly retained with T-hinges and spring loaded cam latches.


Die formed steel housing . White polyester finish.

## 2' x 2'


### T-GRID CEILING



AIR FUNCTIONS	LAMPS	CAT. NO.	VOLTS*	BALLAST*
AIR SUPPLY / RETURN	3-40 W/T5/BX	<b>OPLA-22G-340X-12-</b>	120	ES
STATIC	3-40 W/T5/BX	<b>OPLS-22G-340X-12-</b>	120	ES
HEAT REMOVAL	3-40 W/T5/BX	<b>OPLH-22G-340X-12-</b>	120	ES



AIR SUPPLY / RETURN	3-17 W/T8	<b>OPLA-22G-317-12-</b>	120	ES
	3-20 W/T12	<b>OPLA-22G-320-12-</b>	120	STD
STATIC	3-17 W/T8	<b>OPLS-22G-317-12-</b>	120	ES
	3-20 W/T12	<b>OPLS-22G-320-12-</b>	120	STD
HEAT REMOVAL	3-17 W/T8	<b>OPLH-22G-317-12-</b>	120	ES
	3-20 W/T12	<b>OPLH-22G-320-12-</b>	120	STD



3 x 4 12 CELLS

> For other ceiling type installation see catalog numbering code on PAGE 9, or consult factory.

> Air control / damper blades are available as an option.

\* For other volts and ballast selection = SEE PAGE 9

ORDERING EX: CAT. NO. = **OPLA-22G-317-12-120-ES**