

OPL



OPTILUX 2' x 4' air handling luminaires.

Conforms to VDT lighting criteria.

Ambient lighting balance between VDT task and surrounding area.


Precision formed, 4 1/4" deep cell low iridescent specular aluminum louver.

Louver assembly retained with T-hinges and spring loaded cam latches.

Die formed steel housing .
White polyester finish.

2' x 4'

T-GRID CEILING



3 x 9 27 CELLS

AIR FUNCTIONS	LAMPS	CAT. NO.	VOLTS*	BALLAST*
AIR SUPPLY / RETURN	3-32 W/T8	OPLA-24G-332-27-	120	ES
STATIC	3-32 W/T8	OPLS-24G-332-27-	120	ES
HEAT REMOVAL	3-32 W/T8	OPLH- 24G-332-27-	120	ES
AIR SUPPLY / RETURN	3-40 W/T12	OPLA-24G-340-27-	120	ES
STATIC	3-40 W/T12	OPLS-24G-340-27-	120	ES
HEAT REMOVAL	3-40 W/T12	OPLH-24G-340-27-	120	ES

> For other ceiling type installation see catalog numbering code on PAGE 9, or consult factory.

> Air control / damper blades are available as an option.

* For other volts and ballast selection = SEE PAGE 9
ORDERING EX: CAT. NO. = **OPLA-24G-332-27-120-ES**