

OPL



Air handling luminaires for suspended T-grid ceiling.

Air supply / return, static, and heat removal.

Integrated 6" end filler plates.

4¼" deep cell, precision formed, low iridescent specular aluminum parabolic louver.


Black perimeter reveal around louver assembly.

20" x 48" modules are available (see below).

White polyester finish.

20" x 60"

T- GRID CEILING



2 x 9 18 CELLS

AIR FUNCTIONS	LAMPS	CAT. NO.	VOLTS*	BALLAST*
AIR SUPPLY / RETURN	2-32 W/T8	OPLA-205G-232-18-	120	ES
STATIC	2-32 W/T8	OPLS-205G-232-18-	120	ES
HEAT REMOVAL	2-32 W/T8	OPLH-205G-232-18-	120	ES
AIR SUPPLY / RETURN	2-40 W/T12	OPLA-205G-240-18-	120	ES
STATIC	2-40 W/T12	OPLS-205G-240-18-	120	ES
HEAT REMOVAL	2-40 WT12	OPLH-205G-240-18-	120	ES

>The above luminaires are available for 20" x 48" T-GRID ceiling.

Replace CAT. NO. OPL_205G with OPL_204G-.

>Air control / damper blades are available as an option.

* For other volts and ballast selection = SEE PAGE 9 ORDERING EX: **CAT. NO. =OPLA-205G-240-18-120-ES**