

4PL



Maximum shielding for visual comfort.

4" deep cell , parabolic semi-specular aluminum louver. Mitered interlocked corners.

Air supply / return, static, or heat removal.

Louver retained with T-hinges and spring loaded cam latches.

Air control / damper blades optional with cold air handling units.

Steel housing finished with baked white polyester powder.

12

2' x 4'

T-GRID CEILING

	AIR FUNCTIONS	LAMPS	CAT. NO.	VOLTS*	BALLAST*
<p>2 x 6 12 CELLS</p>	AIR SUPPLY / RETURN		4PLA-24G-232-12-	120	ES
	STATIC	2-32 W/T8	4PLS-24G-232-12-	120	ES
	HEAT REMOVAL		4PLH-24G-232-12-	120	ES
<p>3 x 6 18 CELLS</p>	AIR SUPPLY / RETURN		4PLA-24G-240-12-	120	ES
	STATIC	2-40 W/T12	4PLS-24G-240-12-	120	ES
	HEAT REMOVAL		4PLH-24G-240-12-	120	ES
<p>3 x 6 18 CELLS</p>	AIR SUPPLY / RETURN		4PLA-24G-332-18-	120	ES
	STATIC	3-32 W/T8	4PLS-24G-332-18-	120	ES
	HEAT REMOVAL		4PLH-24G-332-18-	120	ES
<p>4 x 8 32 CELLS</p>	AIR SUPPLY / RETURN		4PLA-24G-340-18-	120	ES
	STATIC	3-40 W/T12	4PLS-24G-340-18-	120	ES
	HEAT REMOVAL		4PLH-24G-340-18-	120	ES
<p>4 x 8 32 CELLS</p>	AIR SUPPLY / RETURN		4PLA-24G-432-32-	120	ES
	STATIC	4-32 W/T8	4PLS-24G-432-32-	120	ES
	HEAT REMOVAL		4PLH-24G-432-32-	120	ES
<p>4 x 8 32 CELLS</p>	AIR SUPPLY / RETURN		4PLA-24G-440-32-	120	ES
	STATIC	4-40 W/T12	4PLS-24G-440-32-	120	ES
	HEAT REMOVAL		4PLH-24G-440-32-	120	ES

> For other ceiling type see catalog numbering code on PAGE 16, or consult factory.

> Air control / damper blades are available as an option.

* For other volts and ballast selection = SEE PAGE 16
ORDERING EX: CAT. NO. = 4PLA-24G-240-12-120-ES