

3PL



Maximum shielding for visual comfort.

3" deep cell, parabolic semi-specular aluminum louver. Interlocked mitered corners.

Air functions, cold air supply / return, static, and heat removal.

Recessed air apertures along 2 sides of luminaire housing.

Louver assembly retained with T-hinges and spring loaded cam latches.

Steel housing, white polyester finish.

14

2' x 2'

T-GRID CEILING	AIR FUNCTIONS	LAMPS	CAT. NO.	VOLTS*	BALLAST*
<p>3 x 3 9 CELLS</p>	AIR SUPPLY / RETURN		3PLA-22G-340X-9-	120	ES
	STATIC	3-40 W/T5/BX	3PLS-22G-340X-9-	120	ES
	HEAT REMOVAL		3PLH-22G-340X-9-	120	ES
<p>3 x 3 9 CELLS</p>	AIR SUPPLY / RETURN		3PLA-22G-331-9-	120	ES
	STATIC	3-31 W/T8/U	3PLS-22G-331-9-	120	ES
	HEAT REMOVAL		3PLH-22G-331-9-	120	ES
<p>4 x 4 16 CELLS</p>	AIR SUPPLY / RETURN		3PLA-22G-417-16-	120	ES
	STATIC	4-17 W/T8	3PLS-22G-417-16-	120	ES
	HEAT REMOVAL		3PLH-22G-417-16-	120	ES
<p>4 x 4 16 CELLS</p>	AIR SUPPLY / RETURN		3PLA-22G-420-16-	120	STD
	STATIC	4-20 W/T12	3PLS-22G-420-16-	120	STD
	HEAT REMOVAL		3PLH-22G-420-16-	120	STD
<p>4 x 4 16 CELLS</p>	AIR SUPPLY / RETURN		3PLA-22G-240-16-	120	ES
	STATIC	2-40 W/T12/U6	3PLS-22G-240-16-	120	ES
	HEAT REMOVAL		3PLH-22G-240-16-	120	ES

> For other ceiling type see catalog numbering code on PAGE 16, or consult factory.

> Air control / damper blades are available as an option.

*For other volts and ballast selection - SEE PAGE 16

ORDERING EX: CAT. NO. = **3PLA-22G-240-16-120-ES**