

RECESSED FLUORESCENT LUMINAIRES FOR T-GRID, DRYWALL, AND METAL PAN CEILINGS

TL



Luminaires with integrated hinged framed diffuser

Steel frame of welded construction, with positive latching.

Latch mechanism activated with finger pressure on lens. To open press lens. To close press frame.

Supplied with no. 12 clear acrylic diffuser. Other lens options available, see PAGE 34.

Interior white reflector.

Steel housing. Baked white polyester finish.

20

1' x 4'

T-GRID CEILING

LAMPS

CAT. NO.

VOLTS* BALLAST*

| | | | | |
|--|------------|-----------------------|-----|----|
| | 1-32 W/T8 | TL-14G-132-12- | 120 | ES |
| | 1-40 W/T12 | TL-14G-140-12- | 120 | ES |
| | 2-32 W/T8 | TL-14G-232-12- | 120 | ES |
| | 2-40 W/T12 | TL-14G-240-12- | 120 | ES |

DRYWALL CEILING

CEILING OPENING REQUIRED 11½" x 48½"

| | | | | |
|--|------------|-----------------------|-----|----|
| | 1-32 W/T8 | TL-14F-132-12- | 120 | ES |
| | 1-40 W/T12 | TL-14F-140-12- | 120 | ES |
| | 2-32 W/T8 | TL-14F-232-12- | 120 | ES |
| | 2-40 W/T12 | TL-14F-240-12- | 120 | ES |

METAL PAN CEILING

| | | | | |
|--|------------|-----------------------|-----|----|
| | 1-32 W/T8 | TL-14M-132-12- | 120 | ES |
| | 1-40 W/T12 | TL-14M-140-12- | 120 | ES |
| | 2-32 W/T8 | TL-14M-232-12- | 120 | ES |
| | 2-40 W/T12 | TL-14M-240-12- | 120 | ES |

HT **SPECULAR**
see page 17

* For other volts and ballast selection = SEE PAGE 34

ORDERING EX: **CAT. NO. = TL-14G-240-12-120-ES**