

RECESSED FLUORESCENT LUMINAIRES FOR T-GRID, DRYWALL, AND METAL PAN CEILINGS

SL



Luminaires with integrated hinged framed diffuser.

Steel frame of welded construction, with positive latching.

Frame is retained with pin hinges and a slide latching device fastened with thumb screws.

Supplied with no. 12 clear acrylic diffuser. Other lens options available, see PAGE 34.

Interior white reflector.

Steel housing. Baked white polyester finish.

2' x 4'

T-GRID CEILING

	LAMPS	CAT. NO.	VOLTS*	BALLAST*
	2-32 W/T8	SL-24G-232-12-	120	ES
	2-40 W/T12	SL-24G-240-12-	120	ES
	3-32 W/T8	SL-24G-332-12-	120	ES
	3-40 W/T12	SL-24G-340-12-	120	ES
	4-32 W/T8	SL-24G-432-12-	120	ES
	4-40 W/T12	SL-24G-440-12-	120	ES

DRYWALL CEILING

CEILING OPENING REQUIRED 23½" x 48½"

	2-32 W/T8	SL-24F-232-12-	120	ES
	2-40 W/T12	SL-24F-240-12-	120	ES
	3-32 W/T8	SL-24F-332-12-	120	ES
	3-40 W/T12	SL-24F-340-12-	120	ES
	4-32 W/T8	SL-24F-432-12-	120	ES
	4-40 W/T12	SL-24F-440-12-	120	ES

METAL PAN CEILING

	2-32 W/T8	SL-24M-232-12-	120	ES
	2-40 W/T12	SL-24M-240-12-	120	ES
	3-32 W/T8	SL-24M-332-12-	120	ES
	3-40 W/T12	SL-24M-340-12-	120	ES
	4-32 W/T8	SL-24M-432-12-	120	ES
	4-40 W/T8	SL-24M-440-12-	120	ES

For **Protected series** with tamper resistant screws and polycarbonate or acrytuf lens consult factory.

HT SPECULAR
see page 17

* For other volts and ballast selection = SEE PAGE 16
ORDERING EX: CAT. NO. =SL-24G-240-12-120-ES