

RECESSED AIR HANDLING FLUORESCENT LUMINAIRES FOR T-GRID CEILING

AST



48" T-GRID MODULE

Cold air handling luminaires for 48" ceiling grid.
Luminaire widths available, 12" - 24",



60" T-GRID MODULE

Cold air handling luminaires for 60" ceiling grid with integrated extension plates.
Luminaire widths available, 12" - 15" - 20" - 60".

Multiple apertures (5) 1/2" x 7/2" on each flange flush with ceiling surface.

Optional blanking covers are available for inactive air functions.

Lay-in no. 12 lens supplied as standard shielding. For other lens and frame options see PAGE 34.

Steel housing, baked white polyester finish.

48" T-GRID CEILING

LAMPS

CAT. NO.

VOLTS* BALLAST*

1' X 4'		2-32 W/T8	AST-14G-232-12-	120	ES
		2-40 W/T12	AST-14G-240-12-	120	ES
2' X 4'		2-32 W/T8	AST-24G-232-12-	120	ES
		2-40 W/T12	AST-24G-240-12-	120	ES
2' X 4'		4-32 W/T8	AST-24G-432-12-	120	ES
		4-40 W/T12	AST-24G-440-12-	120	ES

60" T-GRID CEILING

12" X 60"		2-32 W/T8	AST-125G-232-12-	120	ES
		2-40 W/T12	AST-125G-240-12-	120	ES
15" X 60"		2-32 W/T8	AST-155G-232-12-	120	ES
		2-40 W/T12	AST-155G-240-12-	120	ES
20" X 60"		2-32 W/T8	AST-205G-232-12-	120	ES
		2-40 W/T12	AST-205G-240-12-	120	ES
24" X 60"		4-32 W/T8	AST-245G-432-12-	120	ES
		4-40 W/T12	AST-245G-440-12-	120	ES



Blanking cover for inactive conversion. (2) per section.
CAT. NO. PVC-48

* For other volts and ballast selection = SEE PAGE34
ORDERING EX: CAT. NO. =AST-24G-240-12-120-ES