

## LUMINAIRES FOR SURFACE MOUNTING WITH HOLOPHANE REFRACTORS

# PF



Fluorescent luminaires for surface mounting.  
Up light component reduces ceiling contrast.

Injection moulded clear acrylic wrap-around  
HOLOPHANE refractor with integral end caps.

Concealed spring loaded pin hinges. Refractor  
opens either side for servicing.

Suitable for surface or pendant installations

Steel enclosure, baked white polyester finish.

# 35

	SHIELDINGS	LAMPS	LENGTH	CAT. NO.	VOLTS*	BALLAST*
	HOLOPHANE 6100	1-32 W/T8	48"	PF-4-132-6100-	120	ES
		1-40 W/T12	48"	PF-4-140-6100-	120	ES
		2-32 W/T8**	96"	PF-8-232-6100-	120	ES
		2-40 W/T12**	96"	PF-8-240-6100-	120	ES
	HOLOPHANE 7100	1-32 W/T8	48"	PF-4-132-7100-	120	ES
		1-40 W/T12	48"	PF-4-140-7100-	120	ES
		2-32 W/T8**	96"	PF-8-232-7100-	120	ES
		2-40 W/T12**	96"	PF-8-240-7100-	120	ES
	HOLOPHANE 7100	2-32 W/T8	48"	PF-4-232-7100-	120	ES
		2-40 W/T12	48"	PF-4-240-7100-	120	ES
		4-32 W/T8**	96"	PF-8-432-7100-	120	ES
		4-40 W/T12**	96"	PF-8-440-7100-	120	ES
	HOLOPHANE 7400	2-32 W/T8	48"	PF-4-232-7400-	120	ES
		2-40 W/T12	48"	PF-4-240-7400-	120	ES
	HOLOPHANE 7400	3-32 W/T8	48"	PF-4-332-7400-	120	ES
		3-40 W/T12	48"	PF-4-340-7400-	120	ES
	HOLOPHANE 7400	4-32 W/T8	48"	PF-4-434-7400-	120	ES
		4-40 W/T12	48"	PF-4-440-7400-	120	ES

\*\* TANDEM UNITS

\*VOLTS  
120  
277  
347

\*BALLAST  
ES = ENERGY SAVING  
EL = ELECTRONIC

**HT** **SPECULAR**  
see page 17

ORDERING EX: CAT. NO. = PF-4-240-7400-120-ES