

CEILING MOUNTED SURFACE LUMINAIRES

PEL



Ceiling mounted fluorescent luminaire for indoor application.

Clear acrylic prismatic wrap-around diffuser provides optimum light output.

Suitable for continuous row mounting.

Steel enclosure, baked white polyester finish.

38

SURFACE MOUNTED	LAMPS	LENGTH	CAT. NO.	VOLTS*	BALLAST*
	1-17 W/T8	24"	PEL-41-117-	120	ES
	1-20 W/T12	24"	PEL-41-120-	120	STD
	1-25 W/T8	36"	PEL-41-125-	120	ES
	1-30 W/T12	36"	PEL-41-130-	120	ES
	1-32 W/T8	48"	PEL-41-132-	120	ES
	1-40 W/T12	48"	PEL-41-140-	120	ES
	2-17 W/T8	24"	PEL-41-217-	120	ES
	2-20 W/T12	24"	PEL-41-220-	120	STD
	2-25 W/T8	36"	PEL-41-225-	120	ES
	2-30 W/T12	36"	PEL-41-230-	120	ES
	2-32 W/T8	48"	PEL-41-232-	120	ES
	2-40 W/T12	48"	PEL-41-240-	120	ES
	2-17 W/T8	24"	PEL-51-217-	120	ES
	2-20 W/T12	24"	PEL-51-220-	120	STD
	2-32 W/T8	48"	PEL-51-232-	120	ES
	2-40 W/T12	48"	PEL-51-240-	120	ES
	2-32 W/T8	48"	PEL-61-232-	120	ES
	2-40 W/T12	48"	PEL-61-240-	120	ES
	4-32 W/T8	48"	PEL-61-432-	120	ES
	4-40 W/T12	48"	PEL-61-440-	120	ES

* VOLTS > 120, 277, 347.
 * BALLAST > ES = ENERGY SAVING
 EL = ELECTRONIC
 STD = STANDARD

HT **SPECULAR**
 see page 17

ORDERING EX: **CAT. NO. = PEL-51-240-120-ES**