

MODULAR SURFACE MOUNTED DOWNLIGHTING

LX



Fluorescent downlight for surface mounting.

Frameless lay-in style no. 12 clear acrylic prismatic lens is supplied as standard.

Other lens and frame options available. See below for selections.

Frames are retained with pin hinges, and are of the lift and shift type for removal or servicing.

Steel enclosure, baked white polyester finish.

39

6" x 4'	LAMPS	LENGTH	CAT. NO.	VOLTS*	BALLAST*
	1-32 W/T8	48"	LX-6-132-12-	120	ES
	1-40 W/T12	48"	LX-6-140-12-	120	ES
	2-32 W/T8	48"	LX-6-232-12-	120	ES
	2-40 W/T12	48"	LX-6-240-12-	120	ES
1' x 4'					
	2-32 W/T8	48"	LX-14-232-12-	120	ES
	2-40 W/T12	48"	LX-14-240-12-	120	ES
2' x 2'					
	4-17 W/T8	24"	LX-22-417-12-	120	ES
	4-20 W/T12	24"	LX-22-420-12-	120	STD
	2-31 W/T8/U	24"	LX-22-231-12-	120	ES
	2-40 W/T5/BX	24"	LX-22-240X-12-	120	ES
	2-40 W/T12/U 6"	24"	LX-22-240-12-	120	ES
2' x 4'					
	2-32 W/T8	48"	LX-24-232-12-	120	ES
	2-40 W/T12	48"	LX-24-240-12-	120	ES
	4-32 W/T8	48"	LX-24-432-12-	120	ES
	4-40 W/T12	48"	LX-24-440-12-	120	ES

COMPLETE ORDERING GUIDE > CAT. NO. EX:-

NOTE:
FOR HINGED & LATCHED FRAME -
USE "HL" FRAME DESIGNATION.

LX	22	240	12	00	120	ES
SERIES	MODULE	LAMPS	LENS	FRAME	VOLTS	BALLAST
			12 = NO. 12 PATTERN 19 = NO. 19 PATTERN SL = SILVER LOUVER		120 277 347	ES = ENERGY SAVING EL = ELECTRONIC STD = STANDARD
				00 = FRAMELESS SF = STEEL FLUSH AF = ALUMINUM FLUSH AR = ALUMINUM REGRESSED HL = HINGED AND LATCHED		

HT **SPECULAR**
see page 17