

## SYSTEM FEATURES



- Provides surge protection against harmful transient voltages that exceed the nominal operating voltage of AC and DC critical dedicated control loads
- Ideal for protecting the PLC's, Building management systems, OEM & systems integration controls and other microprocessor-based loads
- Compact, fail-safe design allows flexible installation into electrical/control panels
- Dual Component-Level Fusing (CLF) standard
- Enhanced Transient Filter (ETF) standard
- 15-year Unlimited Free Replacement Warranty
- Reduce lockups, glitches and reprogramming issues

## PRODUCT SPECIFICATIONS

### GENERAL SPECIFICATIONS

**Maximum Rated Surge Current:** 20kA per phase

**Application:** ANSI/IEEE C62.41 Location C, B & A

**Design:** Ultra compact, fail-safe design with dual component-level fusing

**Warranty:** 15-Year Unlimited Free Replacement

**Safety Listing:** ETL recognized component under UL 1449 4th Edition as a type 4 SPD, cETL, and under UL1283 as an electromagnetic filter.

### ELECTRICAL SPECIFICATIONS

**Input Power Frequency:** 47-64Hz

**Maximum Continuous Operating Current:** 30 amps

**Modes of Discrete Suppression Circuitry:**  
All modes L-N, L-G & N-G

**Response Time:** < 1 nanosecond

**Standard Monitoring:** Status indicating light

**Short Circuit Current Rating:** 100kAIC short circuit current rating with a 30 amp max Class T fuse, and 5kAIC with a 30 amp breaker.

### MECHANICAL SPECIFICATIONS

**Dimensions:** 3.94"L x 1.40"W x 2.28"H

**Enclosure:** Polycarbonate Rated V0

**Connection Method:** Hard-wired via box terminals  
#16AWG - #8 AWG

**Mounting Method:** Screw down or Din-Rail mounted.

**Operating Temperature:** -40° C to 85° C (-40° F to 185° F)

**Weight:** 1.00 lbs. (0.45 kg)

### Options:

Dry Relay Contacts: add suffix "-RC". Form C (N/O, N/C) relay contacts rated at 1 amp at 120VAC



### LT PERFORMANCE SPECIFICATIONS

ANSI/IEEE C62.41.1-2002, C62.41.2-2002, & C62.45-2002 Measured Limited Voltage


Model Number (Working Voltage)	Mode	A1 Ring Wave 2kV, 67A 180° Phase Angle	A3 Ring Wave 6kV, 200A 180° Phase Angle	B3/C1 Impulse Wave 6kV, 3kA 90° Phase Angle
TK-LT24-30A-DIN2 (5-30 VAC) (5-38 VDC)	L-N	44V	83V	152V
	L-G	75V	91V	173V
	N-G	50V	85V	173V
TK-LT48-30A-DIN2 (25-50 VAC) (24-65 VDC)	L-N	44V	115V	197V
	L-G	97V	145V	225V
	N-G	49V	117V	193V
TK-LT120-30A-DIN2 (48-150 VAC) (48-200 VDC)	L-N	47V	127V	438V
	L-G	92V	239V	496V
	N-G	47V	128V	470V
TK-LT250-30A-DIN2 (120-260 VAC) (120-300 VDC)	L-N	49V	130V	851V
	L-G	90V	234V	955V
	N-G	48V	130V	960V

All voltages are peak values (+10%) from the zero reference point at the phase angles referenced above using a 10 µs/div display rate and 500MS/s sampling rate. Specifications subject to change without notice, see web site [www.tpsurge.com](http://www.tpsurge.com) for latest revisions.

### EMI/RFI FILTER ATTENUATION—MIL STANDARD

Frequency	Attenuation
1kHz	1dB
10kHz	5dB
100kHz	29dB
1MHz	32dB
10MHz	8dB
20MHz	9dB

All measurements  
in inches [mm]



**For Technical Support**

TEL: 800-853-8265 [www.InnosysPower.com](http://www.InnosysPower.com)